

CAST LED Path Light Module (CALED2): Installation Instructions

Congratulations on your purchase of the CAST LED Path Light Module.

This highly efficient, LED light source is engineered to provide years of trouble-free operation. The following instructions explain how to install the unit and how to apply a conductive grease that will ensure maximum protection for the plug/socket interface.



Apply a thin layer of grease to the end of a cotton swab.*



Using the cotton swab, apply a very thin layer of grease to the two module plug contact wires. Remove excess grease.*

Tools and Materials Needed: -

- ▶ CAST LED Path Light Module (included)
 ▶ Phillips Head Screwdriver
- ▶ Conductive Grease (included)
- ▶ Cotton Swabs (included)



Clean all four socket contacts using cotton swab (with grease). Use up-and-down and twisting motion to scrub contacts. Do not allow grease to contact plastic between contact pairs.*



Apply thin layer of grease to a clean cotton swab. Rub a small amount of grease on each contact. Do not allow grease to contact plastic between contact pairs.*



Firmly insert module plug into socket. Apply pressure until plug clicks into place.



Place module on fixture base so slots line up.



Insert first screw into pathlight hat. Do not tighten - allow wide gap to slide through fixture slot.



Place hat on top of module, sliding hat into position so first screw slides through slot. Insert final screw into place. Use phillips head screw driver to firmly tighten both screws.

*Important: Only a very thin layer of grease is needed. Excess grease can spread between contacts and cause short circuit.