Lighting Specification Sheet

Classic Small Mushroom Area/Path Light (CMU1CB)



Old world craftsmanship. . .tomorrow's technology® _ Date: ______ Project: _____ Fixture Type: _____ Quantity: _____ Specifier: Must operate lamp between 10.5-12.0 5.5" Drawing not to scale volts. Optimal range is 10.8 to 11.3. Check voltage with digital multi-meter. 304 knurled & slotted easy grip thumb screws. Extremely durable solid sand cast Highly reflective white 88-6-3-2 bronze body and cap. underside surface paint. 220°C high-temp teflon-jacketed socket. LED Retrofit: use CALED2-Reflected"no glare" light source. replaces halogen lamp Internal drain stem. CMU1CB: Wedge-base 25 watt Krypton lamp light source. Soldered, crimped and heat shrunk electrical connection to lead wire. 22,0" Heavy duty 100% solid copper fixture stem — .115 wall thickness. ep stake top flush w/grade. _ Install at 90° to grade. Soil #16-2@25' Tin coated Compact backfill in 4" lifts. marine grade No-Ox® wire. Bury wire at 6" depth. **Extremely durable**

Notes

• CMU1CB: Requires S8 Wedge Base Lamp (not included, 25w) Max. lamp rating 35 watts

Coil leftover lead wire at base of fixture. This allows for future field adjustment of fixture placement if required.

- Typical spacing 10' to 15'
- Refer to product installation sheet prior to installation

OPTIONS

- Mounting Canopy Unthreaded (CFM1CBS)
- Standard Mounting Stake (CMS1EM) (incl.)
- Long Mounting Stake (CLMS1EM)
- Heavy Duty Mounting Stake (CHMS1CB)

Unthreaded Stems:

solid bronze stake.

Plan Symbol:

• Telescopic Stem (CWTRS_____)

*NOTE: This is a threaded stake. To use with this fixture, purchase adapter (XCBPTLTA)